

Click to verify

































The store will not work correctly in the case when cookies are disabled. Elevate your pool and landscape experience: expert advice and solutions for seamless enjoyment. Elevate your pool and landscape experience: expert advice and solutions for seamless enjoyment. Vertical Grid: When the filter pressure rises 8-10 PSI over the clean starting pressure, the filter must be backwashed. Turn off the pool pump. Rotate the multiport valve to backwash position or slide the slide valve up. When the pump is turned on, the dirty DE and water will flow out to waste. Once the water runs clear, turn off the pump. With a slide valve, push the handle down and start the pump. Once the pump is primed, add the required DE. If using a multiport valve, rotate the handle to rinse. Turn on the pump and let water flow for 20-30 seconds, cleaning out the plumbing lines. Turn off the pump and rotate the valve back to filter. Turn on the pump and once primed add required DE. Perflex Bump: Perflex filters are unique because they cannot be backwashed. Once the filter pressure rises 8-10 PSI over clean starting pressure, it is time to bump the filter to regenerate the DE. Turn the pump off and grasp the bump handle. Slowly raise the handle then firmly push it down. Repeat this action 3-4 times. Inside the filter the Flex tubes are being raised and lowered, shaking the DE and debris off the tubes. The DE is then sitting on the bottom of the filter. When the pump is turned on, DE will recast the tubes. The filter pressure will not drop to the original starting pressure, but will drop lower than the previous reading. (Example: the original starting pressure was 10 PSI. You bumped the handle when the pressure reached 20 PSI. After the bumping, the pressure dropped to 13 PSI.) The pressure reading after bumping is the new starting pressure. When the pressure goes 8-10 PSI over this, the filter will need to be bumped again. When there is no pressure drop after bumping or the pressure rises very quickly after bumping, the DE will need to be drained and replaced. To replace DE turn off the pump, bump the handle to shake DE off of the tubes and open the drain valve. The pump can be turned on to help expel the dirty DE, but it should be for no longer than a minute. A jet-action cleaning wand can be used to remove any remaining DE. Once a year, the filter should be taken apart and thoroughly cleaned. NOTE: Take a reading of this new clean starting pressure, so you have a reference point for the next backwash cycle. Water may need to be added to the pool to replace the backwashed water. How do I backwash my filter? When the filter pressure rise 8-10 PSI over the clean starting pressure it is time to backwash. Turn the pump off and rotate the multiport valve to backwash. Turn on the pump and the dirty water will flow out the waste line. >> Click to read more